

Boekel Polar Block II

Models 260013 and 260013-2

Features:

- Temperature range -15°C (typical) 35 -39°C below ambient
- Useful for DNA/RNA ethanol precipitations
- Intermediate term storage of restriction enzymes, and other labile reagents
- Active cooling eliminates need to leave samples on the bench too long in ethylene glycol filled freezer blocks

Accessories

- Block Module with block extractor: 7 – 0.5 mL and 7 – 1.5 mL microcentrifuge tubes **Model 260055**
- Block Module with block extractor, 14 – 0.5 mL microcentrifuge tubes **Model 260052**
- Block Module with block extractor, 14 – 1.5 mL microcentrifuge tubes **Model 260152**



Supplied With:

- Block Module: 14 – 1.5 mL microcentrifuge tubes
- Flat plastic lid

	Model 260013 (115 VAC)	Model 260013-2 (230 VAC)
Temperature Range	+/- 15°C (typical) 35°C to 39°C below ambient	
Accuracy	+/- 1° C of set point	
Capacity	1 Block Module	
Overall Dimensions (Width x Length x Height)	24.8 cm x 28.6 cm x 18.4 cm (9.75 in x 11.75 in x 7.25 in)	
Chamber Dimensions (Width x Length x Height)	14.3 cm x 5.7 cm x 5.7 cm (5.75 in x 2.5 in x 2.25 in)	
Shipping Weight	7.71 kg (17 lb)	
Electrical	115 VAC 50/60 Hz 100 W	230 VAC 50/60 Hz 100 W (CE)

Boekel Microcooler II

Models 260010 and 260010-2

Features:

- Temperature range + 4°C to ambient
- Maintains 14°C temperature used in ligation reactions or 17°C for storing oocytes
- "Press to Set" microprocessor controller
- Well is watertight; functions as a small refrigerated bath
- Seamless aluminum pan holds 1.5 mL microcentrifuge rack
- Excellent alternative to messy ice buckets and water baths, which can be a source of contamination
- Useful for cooling blood samples prior to coagulation



Supplied With:

- Rack: 24 – 1.5 mL microcentrifuge tubes
- Flat plastic lid

	Model 260010 (115 VAC)	Model 260010-2 (230 VAC)
Temperature Range	+4°C to ambient	
Accuracy	+/- 1° C of set point	
Capacity	1 Rack	
Overall Dimensions (Width x Length x Height)	24.8 cm x 28.6 cm x 18.4 cm (9.75 in x 11.75 in x 7.25 in)	
Chamber Dimensions (Width x Length x Height)	14.3 cm x 5.7 cm x 5.7 cm (5.75 in x 2.5 in x 2.25 in)	
Shipping Weight	6.7 kg (14 lb)	
Electrical	115 VAC 50/60 Hz 100 W	230 VAC 50/60 Hz 100 W (CE)