





Part Number	00-184-260-000
Applications	STAT Chemistry, Coag, PPP
Max Speed	3,450 xg Max RCF, 4,500 Max RPM
Max Capacity	24 x 75-100 mm/3-10 mL tubes 12 x 125 mm/15 mL tubes 6 x 50 mL tubes
Included	Horizontal Rotor, Buckets, Tube Holders
Warranty	2 years (rotor: lifetime warranty)

# **Loading Angle**



# **Rotation Angle**



# DASH FLEX 24 PROGRAMMABLE STAT CENTRIFUGE

Part # 00-184-260-000

Always know when your STAT samples are ready with the DASH Flex 24 centrifuge. The unique flashing lid lights (patent pending) make it easy to track cycle status and keep TAT down. Customize settings and check every detail on the digital display, and save up to 10 custom cycles to produce high-quality STAT samples.

# **Easy to Monitor**

LED lid lighting indicates when the centrifuge is ready (off), running (on), or done (flashing), reducing forgotten samples and keeping your average TAT down. The DASH Flex 24's digital display shows cycle parameters and time remaining.

## **Easy to Use**

Set and save up to 10 programmable time, speed, and g-force settings using the user-friendly interface. The DASH Flex 24 arrives pre-programmed with the most common STAT settings, and can be easily reprogrammed or adjusted on the fly to meet your lab's specimen processing needs.

#### **High Capacity STAT**

The DASH Flex 24 can spin standard 75-100 mm (3-10 mL) blood tubes, 125 mm (15 mL) long tubes, and tubes with volumes up to 50 mL using a variety of different buckets - no small adapters!

#### **Safe and Durable**

Enjoy years of worry-free operation with the DASH's brushless motor and rugged, reinforced carbon fiber components. Enhance lab safety with imbalance protection and a clear, shatterproof lid, which locks until the centrifuge has stopped completely.

## **A Great Value**

Each DASH centrifuge comes fully equipped and ready to run with a horizontal rotor, universal tube holders, and 2-year warranty included in the affordable price.

# 2-Stage Horizontal Rotor

Our patented swing-out horizontal rotor design incorporates a unique test tube holder that produces the ideal horizontally separated samples.

# **DASH FLEX 24**



# Free 30-Day Evaluation (U.S. Only)

Part Numbers	
Centrifuge	00-184-260-000
Replacement Tube Holders/Buckets	02-004-0-0012K (pack of 6)
50 mL Tube Holders/Buckets	02-004-0-0014K (pack of 6)
Adapters, 1.5 to 2 mL	7713065 (1 qty)
1 yr Warranty Extension	03-0-0007-0003
2 yr Warranty Extension	03-0-0007-0004
3 yr Warranty Extension	03-0-0007-0005

Factory Settings				
	RPM	Time	G-Force	
1st Setting/Cycle	4,300	5 min	3,000 xg	
2nd Setting/Cycle	4,300	6 min	3,000 xg	
3rd Setting/Cycle	3,500	7 min	2,000 xg	

Specifications	
Sound level	61 dBA
Dimensions (W x D x H)	14.5 x 17 x 9 in
	37 x 43 x 23 cm
Weight	31 lbs (14 kg)
Power	100-240 VAC, 50/60Hz
Max Speed/G-Force	4500 RPM/3450 xg













www.boekelsci.com boekel-info@boekelsci.com 215-396-8200, ext 5 800-336-6929, ext 5

