




Part Number 00-676-260-000 Applications STAT Coagulation, Platelet Poor Plasma (PPP) Max Speed 4,400 xg Max RCF, 6,600 Max RPM Max Capacity 12 x up to 75 mm (4 mL) Included Fixed Angle Rotor Warranty 2 years (rotor: lifetime warranty)



DASH COAG SET-AND-LOCK STAT COAG CENTRIFUGE

Part # 00-676-260-000

Reduce turnaround time (TAT) and produce high-quality coags in minutes with the DASH Coag centrifuge. The user-friendly set-and-lock controls streamline STAT lab operations and eliminate errors. Simply select your desired runtime from the DASH Coag's three preset cycles and spin with the press of a button.

Easy to Monitor

Always know when samples are ready with the DASH Coag's LED lid lighting system (patent pending). Bright lights indicate when the centrifuge is ready to load (off), running (on), or done (flashing) and continue flashing until the lid is opened.

Easy to Use

Stop wasting time adjusting settings or navigating complicated menus. The DASH Coag's simple interface makes it easy to select a preset or program your custom validated cycles with the press of a button. Spin tubes up to 75 mm (4 mL) with the same rotor and universal tube holders.

Eliminate Wait Time

Further shorten TAT by using a centrifuge array in accessioning. The array takes advantage of the DASH Coag's compact size to eliminate queuing. Its light weight and small footprint allow it to be easily moved throughout the lab to address bottlenecks.

Safe and Durable

Enjoy years of worry-free operation with the brushless motor and rugged, reinforced carbon fiber components. Enhance lab safety with imbalance protection and a clear, shatterproof lid, which locks until the centrifuge has stopped completely.

A Great Value

Each centrifuge comes ready to run with fixed angle rotor and 2-year warranty included in the affordable price.

Fixed Angle Rotor

The rotor remains at a 45° angle during processing for optimal PPP formation.

DASH COAG



Free 30-Day Evaluation (U.S. Only)

Part Numbers		
Centrifuge	00-676-260-000	
1 yr Warranty Extension	03-0-0007-0003	
2 yr Warranty Extension	03-0-0007-0004	
3 yr Warranty Extension	03-0-0007-0005	

Factory Settings			
	RPM	Time	G-Force
1st Setting/Cycle	6,600	2	4,400
2nd Setting/Cycle	6,600	3	4,400
3rd Setting/Cycle	5,200	5	2,700

Specifications	
Sound level	61 dBA
Dimensions (W x D x H)	11 x 13 x 8 in
	(28 x 34 x 20 cm)
Weight	12 lbs (5.4 kg)
Power	100-240 VAC, 50/60Hz
Max Speed/G-Force	6600 RPM/4400 xg













www.boekelsci.com boekel-info@boekelsci.com 215-396-8200, ext 5 800-336-6929, ext 5

